

CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
SAN FRANCISCO BAY REGION

ORDER NO. 92-140
SITE CLEANUP REQUIREMENTS

CHEVRON U.S.A. PRODUCTS COMPANY
SHELL OIL COMPANY
PS GROUP
SAN FRANCISCO AIRPORT TERMINAL TANK FARM
SAN FRANCISCO INTERNATIONAL AIRPORT
SOUTH SAN FRANCISCO, SAN MATEO COUNTY

The California Regional Water Quality Control Board, San Francisco Bay Region, hereinafter called the Board, finds that:

Description of Discharger

1. Chevron U.S.A. Products Company, Shell Oil Company and PS Group (hereinafter called the Dischargers or Discharger) jointly operate the San Francisco Airport Terminal Tank Farm Facility, a petroleum distribution facility (hereinafter called the Facility) at the San Francisco International Airport. The Facility has historically and is presently used to store refined bulk aviation fuel.
2. The Facility is located at the San Francisco International Airport with access from the airport's perimeter road.

Previous Investigations

3. The Dischargers comprising the facility have jointly monitored 54 ground water wells (1 through 8, inclusive, C-1 through C-22, inclusive, P-1 through P-8, inclusive, S-1 through S-12, inclusive, TF-1, TF-2, OEW and NEW. The discharger has conducted quarterly ground water monitoring and sampling program. The discharger has reported the following results in a Quarterly Status Report dated February 25, 1992:
 - a. The depth to ground water varies from about 1.5 to 8 feet below ground surface;
 - b. Free phase liquid petroleum hydrocarbons were reported to be as thick as 2.38 feet in Chevron's well C-20, as thick as 3.15 feet in PS Group's well P-3, and as thick as 0.67 feet in Shell's TF-2 well; and,
 - c. Concentrations of total petroleum hydrocarbons, benzene, ethylbenzene, toluene and xylene have not be reported; and,
 - d. The operations of recovery wells RW-1 and RW-2 have not been reported.

Cost Recovery

4. The Board's staff has notified the Dischargers that pursuant to Sections 25270.9 and 25270.11 of Chapter 6.67, Division 20 of California's Health and Safety Code the Dischargers shall be liable to the extent of the reasonable costs actually incurred in overseeing or contracting for cleanup or abatement efforts. The Dischargers has agreed to reimburse the State according to Sections 25270.9 and 25270.11.
5. The Dischargers shall also be liable to reimburse the State for its reasonable costs related to cleanup activities, not otherwise reimbursed, pursuant to Section 13304(c) of the California Water Code.

Basin Plan

6. The Board adopted a revised Water Quality Control Plan for the San Francisco Bay Region (Basin Plan) on

December 17, 1986 and amended it on August 19, 1987, July 18, 1989 and December 11, 1991. This Order implements the water quality objectives for the Basin Plan.

Beneficial Uses

7. The existing and potential beneficial uses of the Central San Francisco Bay are:
 - a. Water contact recreation;
 - b. Non-contact water recreation;
 - c. Wildlife Habitat;
 - d. Preservation of Rare and Endangered Species;
 - e. Estuarine Habitat;
 - f. Fish migration and spawning;
 - g. Industrial service supply;
 - h. Navigation; and,
 - i. Commercial and Sport Fishing.
8. The potential beneficial uses of groundwater underlying the site that is deeper than 100 feet are:
 - a. Municipal Supply;
 - b. Industrial Process and Service Supply; and,
 - c. Agricultural Supply.

The shallow aquifer beneath the site has varying water quality. The specific beneficial uses and appropriate cleanup standards for this shallow aquifer will be determined based on technical information to be developed during the investigation and remedial action plan approval process.

California Environmental Quality Act

1. This action is an Order to enforce the laws and regulations administered by the Board. This action is categorically exempt from the provisions of the California Environmental Quality Act pursuant to Section 15321, Title 14, California Code of Regulations.

Notice and Meeting

2. The Board has notified the Dischargers and interested agencies and persons of its intent under California Water Code Section 13304 to prescribe Site Cleanup Requirements for the discharge and has provided them with an opportunity for a public hearing and an opportunity to submit their written views and recommendations.
3. The Board, in a public meeting, heard and considered all comments pertaining to the discharge.

IT IS HEREBY ORDERED, pursuant to Section 13304 of the California Water Code and Section 25270 of the California Health and Safety Code, that the Dischargers shall cleanup and abate the effects described in the above findings as follows:

A. Prohibitions

1. The discharge of wastes or hazardous materials in a manner which will degrade water quality or adversely affect the beneficial uses of the waters of the State is prohibited.

2. Further significant migration of pollutants through subsurface transport to waters of the State is prohibited.
3. Activities associated with subsurface investigation and cleanup which will cause significant adverse migration of pollutants are prohibited.
4. The discharge of recovered free phase liquid petroleum hydrocarbons onto land, into ground waters or surface waters is prohibited.

B. Specifications

1. The storage, handling, treatment or disposal of soil or ground water containing pollutants shall not create a nuisance as defined in Section 13050(m) of the California Water Code.
2. The Dischargers shall conduct free phase liquid petroleum hydrocarbons recovery activities, as needed, to remove all pools of free phase liquid petroleum hydrocarbons beneath the Facility.
3. The Dischargers shall remediate soil and water contamination, which actually or threatens to degrade water quality or adversely affect the beneficial uses of the waters of the State.

C. Provisions

The Dischargers shall comply with the Prohibitions and Specifications above according to the following time schedule:

1. Submission of a technical report, acceptable to the Executive Officer, related to the recovery of free phase liquid petroleum hydrocarbons, including, but not necessarily limited, to the following:
 - a. The horizontal and vertical extent, estimated volume, rate and direction of movement of the free phase liquid petroleum hydrocarbons pool or pools beneath the Facility;
 - b. Evaluation of the free phase liquid petroleum hydrocarbons recovery system including the number, location and removal efficiency of free phase liquid petroleum hydrocarbons recovery well(s); and,
 - c. A remediation plan including a time schedule for remove all free phase liquid petroleum hydrocarbons beneath the Facility.

REPORT DUE: No later than February 17, 1993.

2. Submission of a Technical report, acceptable to the Executive Officer, related to the remediation of contaminated soil and ground water, including, but not necessarily limited, to the following:
 - a. The horizontal and vertical extent of contaminated soil and ground water, rate and direction of movement of the contaminated ground water beneath the Facility; and,
 - b. A remediation plan including a time schedule for all contaminated soil and ground water beneath the Facility.

FINAL REPORT DUE: No later than July 1, 1993.

3. The Dischargers is required to reimburse the State for all reasonable costs of the State incurred in overseeing or contracting for cleanup or abatement efforts.
4. The Dischargers shall maintain a copy of this order at the facility so as to be available at all times to project personnel.
5. The Dischargers's technical reports, as appropriate, shall include a projection of the cost, effectiveness, benefits, and impact on public health, welfare, and environment of each alternative measure. The reports shall consider the guidance provided by the State Water Resources Control Board's Resolution No. 68-16, "Statement of Policy with Respect to Maintaining High Quality of Waters in California".
6. Technical reports, submitted by the Dischargers, in compliance with the Prohibitions, Specifications, and Provisions of this Order shall be submitted to the Board on the schedule specified herein. These reports shall consist of a letter report that includes the following:
 - a. A summary of work completed since submittal of the previous report and work projected to be completed by the time of the next report;
 - b. Identification of any obstacles which may threaten compliance with the schedule of this Order and what actions are being taken to overcome these obstacles;
 - c. In the event of non-compliance with any Prohibition, Specification or Provision of this Order, written notification which clarifies the reasons for non-compliance and which proposes specific measures and a schedule to achieve compliance. This written notification shall identify work not completed that was projected for completion, and shall identify the impact of non-compliance on achieving compliance with the remaining requirements of this Order; and,
 - d. In the first self-monitoring report, an evaluation of the current ground water monitoring system and a proposal for modifications as appropriate.
7. All submittals of hydrogeological plans, specifications, reports, and documents prepared in compliance with the provisions of this Order (except quarterly progress and self-monitoring reports), shall be signed by and stamped with the seal of a registered geologist, registered engineering geologist, or registered professional engineer.
8. All samples shall be analyzed by State certified laboratories or laboratories accepted by the Board using approved EPA methods for the type of analysis to be performed. All laboratories shall maintain quality assurance/quality control records for Board review.
9. The Dischargers shall maintain in good working order, and operate as efficiently as possible, any facility or control system installed to achieve compliance with the requirements of this Order.
10. Copies of all correspondence, reports, and documents pertaining to compliance with the Prohibitions, Specifications, and Provisions of this Order, submitted by the Dischargers, shall also be provided to the following agencies:
 - a. San Francisco International Airport;
 - b. City of South San Francisco;
 - c. San Mateo County Health Department; and,
 - d. California Environmental Protection Agency, Department of Toxic Control Substances.

11. The Dischargers shall permit the Board or its authorized representative, in accordance with Section 13267 (c) of the California Water Code, the following:
 - a. Entry upon premises in which any pollution sources exist, or may potentially exist, or in which any required records are kept, which are relevant to this Order;
 - b. Access to copy all records required to be kept under the terms and conditions of this Order;
 - c. Inspection of any monitoring equipment or methodology implemented in response to this Order; and,
 - d. Sampling of any ground water or soil which is accessible, or may become accessible, as part of any investigation or remedial action program undertaken by the Dischargers.
12. The Dischargers shall file with this Board a report of any material change or proposed change in the character, location, or quantity of this waste discharge. For the purpose of these requirements, this includes any proposed change in the boundaries, contours, or ownership of the disposal areas.
13. The Board considers the property owner and site operator to have a continuing responsibility for correcting any problems within their reasonable control which arise in the future as a result of this waste discharge or water applied to this property during subsequent use of the land for other purposes.
14. These requirements do not authorize the commission of any act causing injury to the property of another or of the public, do not convey any property rights, do not remove liability under federal, state or local laws, and do not authorize the discharge of waste without the appropriate federal, state or local permits, authorizations, or determinations.
15. If any hazardous substance is discharged in or on any waters of the state, or discharged and deposited, or probably will be discharged in or on any waters of the state, the Dischargers shall
 - a. Report such discharge to the following:
 - (1) This Regional Board at (510) 286-1255 on weekdays during office hours from 8 a.m. to 5 p.m.; and,
 - (2) The Office of Emergency Services at (800) 852-7550.
 - b. A written report shall be filed with the Regional Board within five working days and shall contain information relative to the following:
 - (1) The nature of waste or pollutant;
 - (2) The quantity involved and the duration of incident;
 - (3) The cause of spill;
 - (4) The estimated size of affected area;
 - (5) The corrective measures that have been taken or planned, and a schedule of these measures; and,
 - (6) The persons/agencies notified.
16. The Board will review this Order periodically and may revise the requirements when necessary.
17. If the Dischargers is delayed, interrupted or prevented from meeting one or more of the completion

dates specified in this Order, the Dischargers shall promptly notify the Executive Officer and the Board shall consider revision to this Order.

I, Steven R. Ritchie, Executive Officer, do hereby certify the foregoing is a full, true, and correct copy of an Order adopted by the California Regional Water Quality Control Board, San Francisco Bay Region on November 18, 1992.



Steven R. Ritchie
Executive Officer

Attachments:

Figure 1, Site Location Map
Figure 2, Well Location Map
Self Monitoring Program





FIGURE 1
SITE LOCATION MAP



GROUNDWATER
TECHNOLOGY, INC.

**CALIFORNIA REGIONAL WATER QUALITY CONTROL BOARD
SAN FRANCISCO BAY REGION**

SELF-MONITORING PROGRAM

FOR

**CHEVRON U.S.A. PRODUCTS COMPANY
SHELL OIL COMPANY
PS GROUP**

**SAN FRANCISCO AIRPORT TERMINAL TANK FARM, SAN FRANCISCO INTERNATIONAL AIRPORT
SOUTH SAN FRANCISCO, SAN MATEO COUNTY**

SITE CLEANUP REQUIREMENTS

ORDER NO. 92-140

CONSISTS OF

PART A

AND

PART B

PART A

A. General

1. Reporting responsibilities of waste Dischargers are specified in Sections 13225(a), 13267(b), 13383, and 13387(b) of the California Water Code and this Regional Board's Resolution No.73-16.
2. The principal purposes of a self-monitoring program by a waste Dischargers are the following:
 - a. To document compliance with Site Cleanup Requirements and prohibitions established by the Board;
 - b. To facilitate self-policing by the waste Dischargers in the prevention and abatement of pollution arising from waste discharge;
 - c. To develop or assist in the development of standards of performance, toxicity standards and other standards; and,
 - d. To prepare water and wastewater quality inventories.

B. Sampling And Analytical Methods

1. Sample collection, storage, and analyses shall be performed according to the most recent version of Standard Methods for the Analysis of Wastewater, and Test Methods for Evaluating Solid Waste EPA Document SW-846, or other EPA approved methods and in accordance with an approved sampling and analysis plan.
2. Water and waste analysis (except total suspended solids) shall be performed by a laboratory approved for these analyses by the State Department of Health. The director of the laboratory or his duly authorized representative, whose name appears on the certification shall supervise all analytical work in his/her laboratory and shall sign all reports of such work submitted to the Regional Board.
3. All monitoring instruments and equipment shall be properly calibrated and maintained to ensure accuracy of measurements.

C. Definition Of Terms

1. A grab sample is a discrete sample collected at any time.
2. Duly authorized representative is a duly authorized representative may thus be either a named individual or any individual occupying a named position such as the following:
 - a. Authorization is made in writing by a principal executive officer; or,
 - b. Authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity, such as general partner in a partnership, sole proprietor in a sole proprietorship, the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company.

D. Schedule Of Sampling, Analysis, And Observations

1. The Dischargers is required to perform sampling, analysis, and observations according to the schedule specified in Part B, and the requirements in Article 5 of Chapter 15.
2. A statistical analysis shall be performed and reported annually as described in the current revision of Appendix II of Chapter 15.

E. Records To Be Maintained By The Dischargers

1. Written reports shall be maintained by the Dischargers for ground water monitoring and wastewater sampling, and shall be retained for a minimum of three years. This period of retention shall be extended during the course of any unresolved litigation regarding this discharge or when requested by the Board. Such records shall show the following for each sample:
 - a. Identity of sample and sample station number;
 - b. Date and time of sampling;
 - c. Method of composite sampling (See Section C-Definition of Terms);
 - d. Date and time that analyses are started and completed, and name of the personnel performing the analyses;
 - e. Complete procedure used, including method of preserving the sample, and the identity and volumes of reagents used. A reference to a specific section of a reference required in Part A Section B is satisfactory;
 - f. Calculation of results;
 - g. Results of analyses, and detection limits for each analyses; and,
 - h. Chain of custody forms for each sample.

F. Reports To Be Filed With The Board

1. Ground water monitoring results shall be filed monthly until the schedule allows quarterly samples, then reports shall be quarterly. Written self-monitoring reports shall be filed no later than 45 calendar days following the end of the report period. In addition an annual report shall be filed as indicated. The reports shall be comprised of the following:
 - a. Letter of Transmittal - A letter transmitting the essential points in each self-monitoring report should accompany each report. Such a letter shall include a discussion of any requirement violations found during the last report period, and actions taken or planned for correcting the violations, such as, operation and/or facilities modifications. If the Dischargers has previously submitted a detailed time schedule for correcting requirement violations, a reference to the correspondence transmitting such schedule will be satisfactory. If no violations have occurred in the last report period this shall be stated in the letter of transmittal. Monitoring reports and the letter transmitting the monitoring reports shall be signed by a principal executive officer at the level of vice president or his duly authorized representative, if such representative is responsible for the overall operation of the facility from which the discharge originates. The letter shall contain a statement by the official, under penalty of perjury, that to the best of the signer's knowledge the report is true, complete, and correct. The letter shall contain the following certification:

"I certify under penalty of law that this document and all attachments are prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry

of the person or persons who managed the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

- b. Each monitoring report shall include a compliance evaluation summary sheet. Until the Order's amended to specify ground water protection standards, the following shall apply and the compliance sheet shall contain:
 - i. The method and time of water level measurement, the type of pump used for purging, pump placement in the well, method of purging, pumping rate, equipment and methods used to monitor field pH, temperature, and conductivity during purging, calibration of the field equipment, results of the pH, temperature conductivity and turbidity testing, well recovery time, and method of disposing of the purge water; and,
 - ii. Type of pump used, pump placement for sampling, a detailed description of the sampling procedure; number and description of equipment, field and travel blanks; number and description of duplicate samples; type of sample containers and preservatives used, the date and time of sampling, the name and qualifications of the person actually taking the samples, and any other observations; the chain of custody record.
- c. A summary of the status of any remediation work performed during the reporting period. This shall be a brief and concise summary of the work initiated and completed as follows:
 - i. As interim corrective action measures; and,
 - ii. To define the extent and rate of migrations of waste constituents in the soil and ground water at the site.
- d. The Dischargers shall describe, in the quarterly report, the reasons for significant increases in a pollutant concentration at a well onsite. The description shall include the following:
 - i. The source of the increase;
 - ii. How the Dischargers determined or will investigate the source of the increase; and,
 - iii. What source removal measures have been completed or will be proposed.
- e. A map or aerial photograph showing observation and monitoring station locations, and plume contours for each chemical in each aquifer shall be included as part of the quarterly Self-Monitoring Report.
- f. Laboratory statements of results of analyses specified in Part B must be included in each report. The director of the laboratory or his duly authorized representative, whose name appears on the laboratory certification shall supervise all analytical work in his/her laboratory and shall sign all reports of such work submitted to the Board. The following information shall be provided:
 - i. The methods of analyses and detection limits must be appropriate for the expected

concentrations. Specific methods of analyses must be identified. If methods other than EPA approved methods or Standard Methods are used, the exact methodology must be submitted for review; and,

- ii. In addition to the results of the analyses, laboratory quality control/quality assurance (QA/QC) information must be included in the monitoring report. The laboratory QA/QC information should include the method, equipment and analytical detection limits; the recovery rates; an explanation for any recovery rate that is less than 80%; the results of equipment and method blanks; the results of spiked and surrogate samples; the frequency of quality control analysis; and the name and qualifications of the person(s) performing the analyses.

- g. By January 31 of each year the Dischargers shall submit an annual report to the Board covering the previous calendar year. This report shall contain:

- i. Tabular and graphical summaries of the monitoring data obtained during the previous year;
- ii. A comprehensive discussion of the compliance record, and the corrective actions taken or planned which may be needed to bring the Dischargers into full compliance with the Site Cleanup Requirements; and,
- iii. A written summary of the ground water analyses indicating any change in the quality of the ground water.

- G. In the event the Dischargers violates or threatens to violate the conditions of the Site Cleanup Requirements and prohibitions or intends to experience a plant bypass or treatment unit bypass due to:

- 1. Maintenance work, power failures, or breakdown of waste treatment equipment, or;
- 2. Accidents caused by human error or negligence, or;
- 3. Other causes, such as acts of nature.

The Dischargers shall notify the Regional Board office by telephone as soon as he or his agents have knowledge of the incident and confirm this notification in writing within 7 working days of the telephone notification. The written report shall include time and date, duration and estimated volume of waste bypassed, method used in estimating volume and person notified of the incident. The report shall include pertinent information explaining reasons for the noncompliance and shall indicate what steps were taken to prevent the problem from recurring.

In addition, the waste Dischargers shall promptly accelerate his monitoring program to analyze the discharge at least once every day. Such daily analyses shall continue until such time as the effluent limits have been attained, until bypassing stops or until such time as the Executive Officer determines to be appropriate. The results of such monitoring shall be included in the regular Self-Monitoring Report.

Part B

A. Description Of Observation Stations And Schedule Of Observations

1. The observation stations shall consist of all existing ground water monitoring wells (1 through 8, inclusive, C-1 through C-22, inclusive, P-1 through P-8, inclusive, S-1 through S-12, inclusive, TF-1, TF-2, OEW and NEW) and any additional ground water monitoring wells added during the soil and ground water characterization or the evaluation of remediation work.
2. The schedule of well observations and grab sampling shall be conducted within the months of January, April, July and October.
3. The amount of ground water extracted and oil extracted during the quarter and total during this order shall be report quarterly.
4. A map showing the potentiometric surface of the underlying ground water shall submitted quarterly.

B. Observations and Test Procedures


1. The ground water well observations shall consist of the following:
 - a. Water elevation reported to the nearest 0.1 inch for both depth to water from the ground surface and the elevation of the ground water level as well as the elevation of the well screen;
 - b. Ground water temperature measured at the time of sampling and reported in degrees Fahrenheit;
 - c. Ground water conductivity measured at the time of sampling as per Standard Methods 205 using potentiometric methodology;
 - d. Ground water pH measured at the time of sampling as per Standard Methods 423 using potentiometric methodology;
 - e. Ground water turbidity measured at the time of sampling; and,
 - f. The thickness of free phase petroleum hydrocarbons measured in tens of feet.
2. The test procedures for the ground water samples and soil samples shall be as described herein. The following section shall not apply to groundwater samples taken from wells with more than 0.1 inch thickness of free phase petroleum hydrocarbon product:
 - a. Volatile aromatic compound analysis, including benzene, ethylbenzene, toluene, and

xylene using EPA Method 5030/8020;

- b. Total Petroleum hydrocarbons and Fuel Hydrocarbons using the EPA Method 5030/8015 (Modified); and,
 - c. Total Oil and Grease using Standard Methods 418.1. infrared analysis.
3. The operation of the recovery system shall be described, including by not limited to the during of operation of each recovery well, volume recovered and the method of disposal of the recovered material.

I, Steven R. Ritchie, Executive Officer, hereby certify that the foregoing Self-Monitoring Program is as follows:

- 1. Developed in accordance with the procedures set forth in this Board's Resolution No. 73-16;
- 2. Effective on the date shown below; and,
- 3. May be reviewed or modified at any time subsequent to the effective date, upon written notice from the Executive Officer, or request from the Dischargers.



Steven R. Ritchie
Executive Officer

November 18, 1992
Date Ordered